


Medijet

Active/variable flow generator



- A. nCPAP measurement
- B. Driveflow inlet
- C. Outlet port
- D. Drug nebulizer port or
- E. Cap for close down
- F. Benveniste valve
- G. Volume reservoir

Parameters and sensors

CPAP pressures	0 to > 20mbar
Working principle	Beneveniste valve
Noise level	61dB(A)
Volume reservoir ml	4 ml -constant flush
nCPAP pressure	> 4.5cm H ₂ O at 7 l/ml flow

Connectors

Inspiration	10mm OD/7.4 ID
Pressure line	Female connector (similar Luer)

Material

Terlux, Elastollan, PP, TPE-S, Makrolon, PC 10mm OD/ 7,4 ID

Consumables

Interfaces	Prongs and masks in various sizes
Bonnets	Color-coded and different sizes available

Combinable devices

medinSINDI, medinCNO, medinCNOmini, medin-NC3



medin Medical Innovations GmbH
Adam-Geisler-Straße 1
82140 Olching, Germany
☎ +49 (0)8142 448 46 -0
info@medin-medical.com
www.medin-medical.com

REV07
19.05.2025

Specifications are subject to change without notice. Some features are options. Not all features are available in all markets. For all proprietary trademarks (®) and third-party trademarks (®) used by medin Medical Innovations GmbH see www.medin-medical.com/trademarks. © 2025 medin Medical Innovations GmbH. All rights reserved.

Medijet

